

FSS Advanced Layout - Tabs

Error rendering macro 'html'

Your Confluence administrator has disallowed the use of Javascript in the HTML macro. This setting can be changed using HTML for Confluence Configuration. Please see your administrator for details.

All Advanced Layout Examples

[Tabs](#)

[Menus](#)

[Widgets](#)

[Icons](#)

[Layout Fix](#)

FSS Documentation

[Fluid Skinning System \(FSS\)](#)
[FSS Naming Conventions](#)
[FSS Cheat Sheet](#)
[Mobile FSS Cheat Sheet](#)

Demos: [Columns](#)
Demos: [Tabs, Menus, etc.](#)
Demos: [Text](#)
Demos: [Themes](#)

[HTML and CSS Background](#)
[CSS Bugs, Gotchas](#)

Still need help?

Join the [infusion-users mailing list](#) and ask your questions there.

Tabs

The "tabs" classes will convert an unordered list into a set of horizontal tabs. The implementor must create the content divs and programmatically show /hide the divs in response to user input, as well as programmatically move the `fl-tabs-active` class on the currently active tab. The examples on this page are not functional in that sense, and only show one content pane.

Centered Tabs

- [Active Tab](#)
- [Tab #2](#)
- [Tab #3](#)

Content

The mark-up and classes used to produce this layout:

```
<div class="fl-container-600 fl-centered">
  <ul class="fl-tabs">
    <li class="fl-tabs-active"><a href="#_bottom">Active Tab</a></li>
    <li><a href="#_bottom">Tab #2</a></li>
    <li><a href="#_bottom">Tab #3</a></li>
  </ul>
  <div class="fl-tabs-content">
    Content
  </div>
</div>
```

Left-Aligned Tabs

- [Tab #1](#)
- [Active Tab](#)
- [Tab #3](#)

Content

The mark-up and classes used to produce this layout:

```
<div class="fl-container-600 fl-centered">
  <ul class="fl-tabs fl-tabs-left">
    <li><a href="#_bottom">Tab #1</a></li>
    <li class="fl-tabs-active"><a href="#_bottom">Active Tab</a></li>
    <li><a href="#_bottom">Tab #3</a></li>
  </ul>
  <div class="fl-tabs-content">
    Content
  </div>
</div>
```

Right-Aligned Tabs

- [Tab #1](#)
- [Tab #2](#)
- [Active Tab](#)

Content

The mark-up and classes used to produce this layout:

```
<div class="fl-container-600 fl-centered">
  <ul class="fl-tabs fl-tabs-right">
    <li><a href="#_bottom">Tab #1</a></li>
    <li><a href="#_bottom">Tab #2</a></li>
    <li class="fl-tabs-active"><a href="#_bottom">Active Tab</a></li>
  </ul>
  <div class="fl-tabs-content">
    Content
  </div>
</div>
```